

### USB 3.2 Gen 1 USB-C to HDMI Adapter

Models:

U444-06N-HU-C

U444-06N-H3U-C

U444-06N-HGU-C

U444-06N-HGUB-C



Purchased product  
may differ from image.

Este manual está disponible en español en la página de Eaton: [Tripplite.Eaton.com/support](http://Tripplite.Eaton.com/support)

Ce manuel est disponible en français sur le site Web de Eaton : [Tripplite.Eaton.com/support](http://Tripplite.Eaton.com/support)

Dieses Handbuch ist in deutscher Sprache auf der Eaton-Website verfügbar: [Tripplite.Eaton.com/support](http://Tripplite.Eaton.com/support)

Questo manuale è disponibile in italiano sul sito web di Eaton: [Tripplite.Eaton.com/support](http://Tripplite.Eaton.com/support)

# EATON

*Powering Business Worldwide*

## Package Includes

- U444-06N-HU-C, U444-06N-H3U-C, U444-06N-HGU-C or U444-06N-HGUB-C
- Owner's Manual

## Optional Accessories

- P568-Series High-Speed HDMI Cables
- U322-Series USB 3.2 A/B Device Cables
- U326-Series USB 3.2 Micro-B Device Cables
- N201-Series Cat6 Gigabit Snagless Patch Cables
- U420-003 USB 3.2 Gen 1 USB-C Male/Male Cable – 3 ft.

## Product Features

**Note:** This section lists features for all USB Type-C models referenced in this manual. See the **USB Type-C Features** chart to determine which features your model supports.

- Supports USB DisplayPort Alternate Mode for connecting an HDMI monitor via a USB-C port
- HDMI video resolutions supported:
  - All models** – 1920 x 1080/1080p (60 Hz)
  - U444-06N-H3U-C model only** – 3840 x 2160/4K x 2K (30 Hz)
- Ethernet port supports true 10/100/1000 Mbps network speeds

## Product Features

- USB-A hub port supports data transfer rates up to 5 Gbps; backward compatible with previous USB generations
- USB-C charging port for charging your device
- USB-C port power input:
  - **U444-06N-HU-C, U444-06N-HGU-C, U444-06N-HGUB-C models** –  
Up to 20V 3A (60W)
  - **U444-06N-H3U-C model** –  
Up to 20V 5A (100W)
- Plug and play; no software or drivers required

## USB Type-C Features

Models	U444-06N-HU-C	U444-06N-HGU-C / U444-06N-HGUB-C	U444-06N-H3U-C
HDMI Port	Y	Y	Y
USB-A Hub Port	Y	Y	Y
Gigabit Ethernet Port	N	Y	N
USB-C Charging Port	Y	Y	Y

**Note:** The U444-06N-H3U-C features three USB-A hub ports.

## Installation

**Note:** When the unit is connected to the USB-C port on your computer and to a network via Cat5e/6 cabling, a network connection will be automatically established. If no connection is made, you can manually establish one by going to your computer's network settings page. For example, on a Mac you would navigate to the Network section found in System Preferences, click the 'Assist Me' button to get to the Network Setup Assistant, then follow the prompts to establish a connection.

1. Connect the adapter's USB Type-C connector to the USB-C port on your laptop, tablet or other compatible device.
2. Connect the adapter's HDMI port to the monitor's HDMI port using an HDMI cable (such as P568-Series HDMI cables).
3. Charge your device by connecting its USB-C charger to the adapter's USB-C port.
4. Connect a USB device to the adapter's USB-A hub port.\*
5. Connect the adapter's RJ45 port to a network using a UTP cable (such as N201-Series Cat6 cables).\*

\*See the **USB Type-C Features** chart for the features your product supports.

## Specifications

Models	U444-06N-HU-C	U444-06N-HGU-C / U444-06N-HGUB-C	U444-06N-H3U-C
<b>Input Connectors</b>			
USB	USB-C (Male)	USB-C (Male)	USB-C (Male)
Charging	USB-C (Female)	USB-C (Female)	USB-C (Female)
<b>Output Connectors</b>			
HDMI	HDMI (Female)	HDMI (Female)	HDMI (Female)
USB	USB-A (Female)	USB-A (Female)	USB-A (Female) x 3
Ethernet	N/A	RJ45 (Female)	N/A
<b>Environmental</b>			
Operating Temperature	32°F to 113°F (0°C to 45°C)		
Operating Humidity	10% to 85% RH, Non-Condensing		
Storage Temperature	14°F to 158°F (-10°C to 70°C)		
Storage Humidity	5% to 90% RH, Non-Condensing		
<b>Power Requirements</b>			
USB-C Charging Port	Supports up to 20V 3A (60W) Input	Supports up to 20V 5A (100W) Input	
USB 3.2 Port	Provides up to 5V 1A (5W) Output	Provides up to 5V 1.5A (7.5W) Output	

# Warranty

## **3-YEAR LIMITED WARRANTY**

We warrant our products to be free from defects in materials and workmanship for a period of three (3) years from the date of initial purchase. Our obligation under this warranty is limited to repairing or replacing (at its sole option) any such defective products. Visit [Triplite.Eaton.com/support/product-returns](http://Triplite.Eaton.com/support/product-returns) before sending any equipment back for repair. This warranty does not apply to equipment which has been damaged by accident, negligence or misapplication or has been altered or modified in any way.

EXCEPT AS PROVIDED HEREIN, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Some states do not permit limitation or exclusion of implied warranties; therefore, the aforesaid limitation(s) or exclusion(s) may not apply to the purchaser.

EXCEPT AS PROVIDED ABOVE, IN NO EVENT WILL EATON BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS PRODUCT, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. Specifically, we are not liable for any costs, such as lost profits or revenue, loss of equipment, loss of use of equipment, loss of software, loss of data, costs of substitutes, claims by third parties, or otherwise.

## **FCC Notice, Class B**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment

## Warranty

is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense. The user must use shielded cables and connectors with this equipment. Any changes or modifications to this equipment not expressly approved by Eaton could void the user's authority to operate this equipment.

### WEEE Compliance Information for Tripp Lite Customers and Recyclers (European Union)



Under the Waste Electrical and Electronic Equipment (WEEE) Directive and implementing regulations, when customers buy new electrical and electronic equipment from Eaton, they are entitled to:

- Send old equipment for recycling on a one-for-one, like-for-like basis (this varies depending on the country)
- Send the new equipment back for recycling when this ultimately becomes waste

Use of this equipment in life support applications where failure of this equipment can reasonably be expected to cause the failure of the life support equipment or to significantly affect its safety or effectiveness is not recommended. Do not use this equipment in the presence of a flammable anesthetic mixture with air, oxygen or nitrous oxide.

Eaton has a policy of continuous improvement. Specifications are subject to change without notice.



Eaton  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

© 2023 Eaton  
All Rights Reserved  
Publication No.  
23-08-065 /  
93-357E\_RevF  
August 2023

Eaton is a registered  
trademark.

All trademarks are  
property of their  
respective owners.